



Technical Data Sheet

CRAMOLIN® SPRAYWASH Art. No.105

Product description

SPRAYWASH contains a powerful mixture of solvents that ensure gentle but effective removing of dirt and grease. The product's good penetration and flowing properties enable SPRAYWASH to wash away any soiling without difficulty. It does not attack any material in common use, and evaporates completely after a short time without leaving any residue. SPRAYWASH has been developed especially for the cleaning of dissolved oxide layers after having used CONTACTCLEAN.

Application

Intensive cleaning of contacts, components and appliances in electrical engineering, especially on switches, electric motors, relays, contactors, cabinets, etc. Also to be used to wash out oxide and sulphide layers on contact surfaces previously dissolved by CONTACTCLEAN.

Spray SPRAYWASH thoroughly on surfaces to be cleaned. Ensure uniform wetting of these surfaces. Adjust quantity of SPRAYWASH to degree of dirtiness. For spots of difficult access, use the attached extension tube. Spray at intervals, avoid continuous spraying.

Please note

Electronical devices to be switched-off during cleaning and plug to be taken out.

Cleaning instructions of appliance producer to be taken into account.

Further information concerning SPRAYWASH to be found in recent MSDS.



Technical Data

Appearance:	clear, colorless liquid
Odor:	characteristic
Density at 20° C:	0,75 [g/cm ³]
Material compatibility:	good
Evaporation:	average
Surface tension:	23 [mN/m]

Storage / Shelf Life

Shelf life is 2 years if stored correctly.

Package after emptying to be disposed via metal scrap.